

STRIPE WHITE™

White Line Marking Paint



DESCRIPTION

Stripe White™ is a durable, efficient surface coating made of 100% acrylic emulsion paint, especially designed for line marking

tennis courts, running tracks and other asphalt or concrete surfaces.

USES

Stripe White™ was especially designed for line marking tennis courts, running tracks and other asphalt or concrete surfaces.

PRODUCT ADVANTAGES

- Waterproofs.
- Prevents glare.
- Resists abrasion & scuffing.
- Beautifies.
- Easy to apply.

YIELD/COVERAGE

- One gallon covers 500-600 lineal feet of 2-inch line per gallon.

SURFACE PREPARATION

All dirt, oil, dust, foreign contaminants, peeling coating and laitance must be removed from surface prior to coating to assure a trouble free bond. Previously coated floors exhibiting a strong bond to surface can be coated over by sanding down the existing coating.

Refer to Garon's Master Surface Preparation & Moisture Guideline for complete details.

MIXING AREA

Select a suitable mix area and protect the floor surface from accidental resin spillage with a layer of cardboard and/or plastic sheet. Provide enough space for free unimpeded movement for mixing activity. The more comfortable your surroundings in the mix area, the less likely your mixers are to have an error. Have all necessary tools ready: slow speed drills, mix and measure containers, etc. **Do Not Start Mixing Materials Until Ready for Immediate Use.** Once hardener and resin are combined, it must be used immediately. Prior to mixing apply masking tape wherever coating is intended to stop. Keyed edges must be installed at edge termination points to

protect the material from chipping damage and to obtain a clean, straight edge.

MIXING

Stir well before using. Apply as is or modify to match the existing texture of the court surface by adding 80 to 100-mesh silica sand.

APPLICATION & PLACEMENT

Stripe White™ can be rolled, brushed or sprayed with low pressure spraying equipment. To assure crisp lines, it is advisable to

use high quality tape to mask lines. Remove tape as soon as Stripe White™ has dried.

SET TIME

Stir before using. Thirty to sixty (30-60) minutes under optimum drying conditions. Indoor applications are substantially affected by temperature and available ventilation and will dry more slowly. Temperatures must be above 50 degrees F both during and after application for a period of at least 24 hours. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use.

NOTE: For best results, courts should have a sound, well-drained base of adequate thickness and stability. Existing surfaces should be properly sloped for good drainage, and free from cracks. On outdoor concrete surfaces, assure adequate and functional perimeter drains as well as a sound vapor barrier beneath the slab.

CHEMICAL RESISTANCE

This product is resistant to most common chemicals. Please refer to **Garon's Chemical Resistance Chart** for actual resistance to specific chemicals/reagents.

SLIP & FALL HAZZARDS

Ensure cured coating surface remains dry in pedestrian, equipment and vehicular areas to avoid slips and falls of people, equipment and vehicles. Use caution when coating is wet or when oil, hydraulic fluids, grease or other chemicals, fluids or agents that may produce a slick surface are present. Increase slip resistance by broadcasting an appropriate size aggregate into the wet coating during application in all areas where enhanced coating traction may be

GARON

necessary. **Be aware of the full cure time. Do not open the area to normal service, harsh industrial chemical or abusive use before the coating is fully cured.**

CLEAN UP

Contain spills. Ventilate area. Use absorbent materials to collect. Dispose of according to local, state, federal regulations. Mixed components — uncured material can be removed with an approved xylene or keytone solvent. Cured material must be removed by mechanical means.

DISCLAIMER

The information and recommendations set forth in this document are based upon tests conducted by or on behalf of Garon Products, Inc. Such recommendations and information set forth herein are subject to change and pertain to the product(s) offered at the time of publication. Published technical data and instructions are subject to change without notice. Consult www.garonproducts.com or call 800-631-5380 to obtain the most recent Product Data, SDS and Application instructions. This is not a controlled document.

COLOR

Applied samples, color charts, illustrations and reproductions in catalogs and other Garon publications are not guaranteed to match the color shades of materials ordered. Colors or clarity for clear may be affected by high humidity, low temperatures, or chemical exposure. Tire contact may cause discoloration. Slight lot-to-lot color variations may occur. Light or bright colors (white, safety yellow, etc.) may require multiple coats or a suitable color coordinated primer to achieve a satisfactory hide. When ordering to match a previous color, inquire if the same lot number or quality control number is still available. Colors may vary from batch to batch, therefore, use only product from the same batch for an entire job.

FIRST AID

Skin contact- wash thoroughly with soap & water. If any product gets into the eye, rinse immediately and repeatedly with water for at least 15 minutes. For respiratory problems, remove person to fresh air. Wash clothing before re-use.



Dust may cause skin or eye irritation. Wear gloves, eye and nuisance protection. **CONSULT SDS** and call for medical care if necessary.

LIMITATIONS

The user is responsible for proper application.

CAUTION

Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed.

Keep container tightly closed. Not for internal consumption--consult MSDS for additional information. This product is for professional use only.

KEEP OUT OF REACH OF CHILDREN

Garon and **Stripe White™** are trademarks of Garon Products Inc.
Made in USA.

GARON PRODUCTS INC.

P.O. Box 1924
Wall, NJ 07719-1924
800-631-5380
FAX 732-223-2002

www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and seller.